



ABR GD:- GLASS DOOR BENCH REFRIGERATOR SERIES





ABR Series

FEATURES:

- SHAMROCK 's GLASS DOOR BENCH TOP REFRIGERATORS are designed with the commercial kitchen in mind.
- Operating Temperature o° to +5° C. Climate Type N.
- Only requires one a standard power point (GPO):- 240V 50Hz 10 amp.
- Digital Temperature Display.
- 1 height adjustable shelf per door.
- Stainless steel fascia and outer sides.
- Powder coated aluminum inner walls and clear anodized aluminum outer back.
- Stainless steel internal floor with coved corners allows for easy cleaning and sanitizing.
- Extra Large castors, for ease of cabinet movement.
- Low E Glass Door, Designed with horizontal handle and self closing torsion bar hinging.

MAIN DATA

Specifications are subject to change without notice. E&OE.

Model	Doors	Volume (Gross lts)	Shelves	Height (mm)	Width (mm)	Depth (mm)	Voltage	Power Outlet	Cord Length	Shipping Weight
ABR1225	2	340	1	910	1225	770	240v/50hz	10amp	2.4	136kg
ABR1555	2	440	1	910	1555	770	240v/50hz	10amp	2.4	157Kg

Head Office: Unit 1/35 Rimfire Drive ,Hallam, Vic 3803. Phone: 1800 813 987 Fax: 03 8786 3572 Email: sales@austwiderentals.com websites: www.austwidesales.com.au or austwiderentals.com SHAMROCK



ABR GD:- GLASS DOOR BENCH REFRIGERATOR SERIES

Outstanding Benefits

- Fitted with full width doors, offering maximized face area for storing your inventory. This allows increased visibility and hence ergonomic picking of inventory.
- ABR GD Series is paired with the • ABR and ABF series of Block door refrigerators and freezers.

Specification

- Refrigeration System: Fully balanced self contained condensing unit with forced draught evaporator.
- Condensing unit: Located at rear. Unit access from back of cabinet, Quality castors allow easy roll out of cabinet allowing access for condenser cleaning and maintenance.
- Refrigerant: R134A.
- Defrost: Cyclic defrost, with nocost, hot gas condensate disposal. Supplemented with timed defrosts via electronic controller.
- Electronic Controller: Italian designed, Dixell temperature controller and digital display. Includes high temp alarm.
- Evaporator: Epoxy coated to eliminate the potential of corrosion and thus future gas leaks.
- Shelves: 1 height adjustable, PVC

coated, shelf per door. 4 stainless steel shelf clips per shelf fit to stainless steel shelf posts.

- **Operation conditions:** 0° to 5° C. at up to 32° C ambient.
- Electrical: Units come ready for connection to 240volt 50hz 10amp GPO. Single Outlet. It is recommended that a dedicated GPO be used.
- Construction: Stainless Steel doors, front and sides provide a clean and dent resistant cabinet. Clear anodized aluminum back. Interior white powder coated aluminum for hygienic easy to clean surfaces.
- Stainless Steel inner tray designs with coved corners for easy cleaning.
- Insulation: 50mm high density polyurethane foamed in place, Blowing agent, Cyclopentane for CFC free Ozone protection and superior insulating properties. .
- **Door:** Double glazed Low E glass doors with aluminum frame. Hinging: Self closing with a dwell open position for easy loading and unloading. Gasket: PVC welded one piece

magnetic gasket. Removable without the need for tools.

Castors: 4 (2 x locking) x 75mm

swivel heavy duty castors.

Warranty1: Austwide's Manufacturers warranty 12 month parts and labour. See terms and conditions of sale for full description.


Details	ASP775	ASP1225	ASP1555	
Volume (L)	184	340	440	
Shelf Area (m ²)	1.3	2.42	2.79	
Capacity (watts)	820	880	940	

1.terms and conditions apply. Visit web site for full details. www.austwidesales.com.au Specifications are subject to change without notice. E&OE.

NOTE: excluding the width all dimensions on the Elevations are common across the ASP GD Series.

Model	Width
ABR1225	1225mm
ABR1555	1555mm

ELEVATIONS. (not to scale)



Head Office: Unit 1/35 Rimfire Drive ,Hallam, Vic 3803. Phone: 1800 813 987 Fax: 03 8786 3572 Email: sales@austwiderentals.com websites: www.austwidesales.com.au or austwiderentals.com